

Архангельск (8182)63-90-72  
Астана (7172)727-132  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89  
Иваново (4932)77-34-06

Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Липецк (4742)52-20-81  
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Казахстан (772)734-952-31

Пермь (342)205-81-47  
Россия (495)268-04-70  
Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35  
Тверь (4822)63-31-35  
Томск (3822)98-41-53  
Тула (4872)74-02-29  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Ярославль (4852)69-52-93

<https://nuoying.nt-rt.ru/> || [nyo@nt-rt.ru](mailto:nyo@nt-rt.ru)

## Волноводный радарный уровнемер NYRD-704 NYRD-704 Guided Wave Radar Level Sensor



### Design features

Guided wave radar level gauge adopts advanced microwave processing technology and unique Echo Discovery echo processing technology. Contact measurement has high accuracy and more accurate measurement. At the same time, guided wave radar is anti-adhesion, not affected by external environment such as medium temperature and adhesion.

The 70X series guided wave radar level gauge is suitable for various complex working conditions and application occasions due to various process connection modes and detection components. For example, high temperature, high pressure and low dielectric constant medium, etc.

Using pulse mode, the product can be installed in all kinds of metal and non-metal containers with very low emission power, which is harmless to human body and environment.

Application: Complex occasions such as low dielectric constant and stirring, Liquid

Antenna material: 304

Measuring range: 6 meters

Frequency range: 1.8GHz

Accuracy:  $\pm 1$ mm

Medium temperature: -40 to +130 °C

Process pressure: -0.1~0.3Mpa

Power supply: 24VDC (two-wire, four-wire optional)

Signal output: 4...20mA/HART (two lines/four lines)/ RS485/Mod bus

Process connection: Flange/Thread

Protection level: IP67

Explosion-proof grade: Exia IIC T6 Ga