

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-31

Пермь (342)205-81-47
Россия (495)268-04-70
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://nuoying.nt-rt.ru/> || nyo@nt-rt.ru

Интеллектуальный радарный уровнемер NYRD-803T

NYRD-803T Intelligent Radar Level Transmitter



Intelligent Radar Level Sensor

1. Design features:

Intelligent radar level sensor adopts advanced microwave processing technology and unique Echo Discovery echo processing technology. The product can be applied to various complex working conditions.

The function of "false echo learning" enables the instrument to accurately identify the real echo under the condition of multiple false echoes, so as to obtain accurate measurement results.

Various process connection modes and detection components can be customized according to customer requirements.

With pulse mode, the product can be installed in all kinds of metal and non-metal containers with very low emission power, which is harmless to human body and environment.

2. Technical parameters

Application: Liquid, agitated, low dielectric constant liquid

Antenna material: 304

Measuring range: 35 meters

Frequency range: 6.8GHz

Accuracy: $\leq 0.1\%$ FS

Medium temperature: -40 to +300 °C

Process pressure: -0.1~4.0Mpa

Power supply: 24VDC (two-wire, four-wire optional)

Signal output: 4...20mA/HART (two lines/four lines)/ RS485/Mod bus

Process connection: Flange

Protection level: IP67

Explosion-proof grade: Exia IIC T6 Ga