

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-31

Пермь (342)205-81-47
Россия (495)268-04-70
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://nuoying.nt-rt.ru/> || nyo@nt-rt.ru

Интеллектуальный контроллер цифрового дисплея Intelligent digital display controller



Intelligent digital display controller

Design characteristics

1. NYKS-X series digital display intelligent control instrument adopts the microprocessor to carry on the control operation, can carry on the extremely high precision linear correction measurement to the various nonlinear input signal, makes the measurement value display clearer and intuitionistic;
2. NYKG-X series optical column display intelligent control instrument integrates digital and analog, it can display digital signal and analogue signal (optical column display), which makes the display of measurement value more clear and intuitive. At the same time, it can also choose double optical column display;
3. The product model is many, can satisfy the spot working condition demand, the application scope is wide;
4. Simple structure, convenient installation and customizable design.

Parameters:

Display range: -1999~9999

Measurement accuracy: 0.2%FS \pm 1 word, 0.5%FS \pm 1 word

Control mode: three-bit return difference

Operating environment: temperature 0 ~ +50 °C

Input signal: thermal resistance: Pt100, Cu

Thermocouple: T, R, J, Wre3-25 B, S, K, E

Standard signal: 0~375 Ω 、0~75mV、0~30mV、0~5V
1~5V、0~10V、0~10mA、0~20mA、4~20mA

Switch output: 250VAC / 3A, 24VDC / 5A

Analog output: 0~5VAC, 0~10VDC, 0~20mA, 4~20mA

Feed output: 24VDC/30mA

Power supply: (85~260) VDC/AC

Communication interface: RS-232, RS-485

Alarm mode: optional relay up and down alarm output

Set / display: panel keystroke digital settings, numerical
power loss permanent hold